

2

3

4

5

6

7

REVISION DATA		
REV	DESCRIPTION	DATE
A0	NEW DRAWING	16-5-17

Technical Data

Material:

Pin(outer sleeve):Brass, machined CuZn38Pb2

Plating(outer sleeve):

Tin Plated:2μm/80μm"Ni, 5μm/200μ"Sn

Gold Plated:2μm"/80μm"Ni, 0.8μ" gold

Plating(Contact ):2μm/80μ"Ni, gold or Tin plated

Insulator:PPS UL94V-0

Clip(Contact 4 Finger):Beryllium copper,heat treated

Electrical:

Current rating:3Amps/contact max.

Contact resistance: ≤4mΩ/contact

Insulation resistance: ≥1000MΩ at V=100V

Operating voltage:60VAC/DC

Mechanical:



Average Insertion force with steel pin of ∅0.432: <250g

Average withdrawal force with steel pin of ∅0.432: >70g

Mechanical life cycle:min 200

Operating temperature:-40 ° C to+105 ° C

Soldering temperature:+255 ° C



QZT	X	X	XXX	X	XX	XXXX	X
Pitch(mm) A=2.54X2, 54 B=2.54X1, 27 C=1.27X1, 27	Angel Options P=PA C1=PLCC-SMT C2=PLCC-DIP	No. of Positions XXX positions 329=329PIN	Pin plated T1=Tin 150u" T2=Tin 200u" G1=6/F G2=Gold 3u" G3=Gold 10u" G4=Gold 15u" G5=Gold 30u"	CLIP plated T1=Tin 150u" T2=Tin 200u" G1=6/F G2=Gold 3u" G3=Gold 10u" G4=Gold 15u" G5=Gold 30u"	Pin Length Options 07/40=7.40mm	Specifications A=Public seat B=Female seat	

**dzconn** 东莞市启之泰电子科技有限公司  
 启之泰

TOLERANCE	PROJECTION	TITLE:
X,XXX ±0.05		Pin grid array sockets
X,XX ±0.15	DATE: 2016-5-17	2.54x1.27mm 329PIN
X,X ±0.20	DRAWN: TANG-S-G	PART NO: QZTB-P329XXXX0740B
X, ±0.30	CHECKED:	DRAWING NO:2016051704
ANGLE ±5.0°	APPROVED:	REV: A0 UNIT: mm SCALE: 1:1 SIZE: A4 PAGE: 1/2