

REVISION DATA		
REV	DESCRIPTION	DATE
A0	NEW DRAWING	16-4-05

Technical Data




Material: Pin(outer sleeve): Brass, machined CuZn38Pb2
 Plating(outer sleeve):
 Tin Plated: 2μm/80μm"Ni, 5μm/200μ"Sn
 Gold Plated: 2μm"/80μm"Ni, 0.8μ" gold
 Insulator: PPS UL94V-0

Electrical:

Current rating: 3Amps/contact max.
 Contact resistance: $\leq 4m\Omega$ /contact
 Insulation resistance: $\geq 1000M\Omega$ at V=100V
 Dielectric Withstanding Voltage: 1000V AV Min
 Operating voltage: 60VAC/DC

Mechanical:

Operating temperature: -40 ° C to +105 ° C
 Soldering temperature: +255 ° C



P. C. B LAYOUT

QZT	X	X	-	X	XX	XX	XXXX	X
Pitch (mm) A=1.27 B=1.778 C=2.00 D=2.54	Insulator Type code 1=Single row 2=Double row 3=Three row	Angel Options D=180° R=90° S=SMT I=IC	No. of Positions XX positions	Pin plated T1=Tin 150u" T2=Tin 200u" G1=G/P G2=Gold 3u" G3=Gold 10u" G4=Gold 15u" G5=Gold 30u"	Pin Length Options 1000=10.00mm	Specifications A=Public seat B=Female seat		

Qztconn 东莞市启之泰电子科技有限公司
 启之泰

TOLERANCE	PROJECTION	TITLE:
X,XXX ±0.05 X,XX ±0.15 X,X ±0.20 X, ±0.30 ANGLE ±5.0°	DATE: 2016-4-05 DRAWN: TANG-S-G CHECKED: APPROVED:	Socket Connectors 2.54mm L=10.00mm ø0.45 PART NO.: QZTD1-DXXXX1000A-1 DRAWING NO.: 2016040509